



ROMPEDORA DE BLOQUES CONGELADOS MOD. FR-B1

La rompedora de bloques congelados FR-B1 está diseñada para la separación eficaz de bloques de producto congelado en sus distintas capas.

El sistema de accionamiento hidráulico aplica una presión precisa, uniforme y controlada, permitiendo la rotura del bloque de forma eficiente sin dañar productos frágiles como pescado y cefalópodos.

Su integración en acero inoxidable y su diseño preparado para entornos de alta humedad aseguran durabilidad, resistencia y facilidad de limpieza en aplicaciones industriales del sector alimentario.

FROZEN PRODUCT BLOCK BREAKER MOD. FR-B1

The FR-B1 frozen block breaker is designed for the efficient separation of frozen product blocks into their different layers.

Its hydraulic system applies precise and controlled pressure, allowing the block to be broken efficiently while preventing damage to delicate products such as fish and cephalopods.

Its stainless steel construction and moisture-resistant design ensure durability, reliability and easy cleaning in demanding food processing environments.

ROMPEDORA DE BLOQUES

Una vez posicionada la pieza, el operario acciona los pulsadores de mando, activando el cilindro hidráulico, que ejerce la presión necesaria para romper el bloque de forma eficaz y uniforme.

CARACTERÍSTICAS TÉCNICAS

- Construcción en acero inoxidable
- Sistema de accionamiento hidráulico
- Cilindro hidráulico en acero inoxidable
- Instalación eléctrica con cuadro de maniobra a 24 V
- Panel de maniobra estanco
- Accionamiento mediante pulsadores
- Protección elevada frente a la humedad
- Fácil mantenimiento
- Limpieza simple y rápida

BLOCK BREAKER

Once the block is positioned, the operator activates the push-buttons, engaging the hydraulic cylinder, which applies the required pressure to break the block in an efficient and controlled manner.

TECHNICAL SPECIFICATIONS

- Stainless steel construction
- Hydraulic drive system
- Stainless steel hydraulic cylinder
- Electrical installation with 24 V control panel
- Watertight control panel
- Push-button operation
- High protection against moisture
- Easy maintenance
- Simple and fast cleaning

TIPOS	FR - B1	TYPES
Largo	1.300 mm	Length
Ancho	800 mm	Width
Alto total	1.000 mm	Height
Altura de trabajo	760 mm	Working height
Potencia	2,5 CV (1.84 kW)	Power
Dimensión máx. bloque	800 x 500 mm	Max. block dimensions