

BROCA MANGO CILÍNDRICO

DIN 1869

Aplicaciones

Aceros 400-800N/ mm2



DIAMETRO	L. TOTAL	L. CORTE	DIAMETRO	L. TOTAL	L. CORTE	DIAMETRO	L. TOTAL	L. CORTE
2.00	125	85	7.00	225	155	10.00	430	295
2.50	140	95	7.00	290	210	10.50	265	185
3.00	150	100	7.00	370	250	10.50	340	235
3.00	190	130	7.50	225	155	10.50	430	295
3.50	165	115	7.50	290	200	11.00	280	195
3.50	210	145	7.50	370	250	11.00	340	250
3.50	265	180	8.00	240	165	11.00	455	310
4.00	175	120	8.00	305	210	11.50	280	195
4.00	220	150	8.00	390	265	11.50	340	250
4.00	280	190	8.50	240	165	11.50	455	310
4.50	185	125	8.50	305	210	12.00	295	205
4.50	235	160	8.50	390	265	12.00	375	260
4.50	295	200	9.00	250	175	12.00	480	315
5.00	195	135	9.00	320	220	12.50	295	205
5.00	245	170	9.00	410	280	12.50	375	260
5.00	315	210	9.50	250	175	12.50	480	315
5.50	205	140	9.50	320	220	13.00	295	205
5.50	260	180	9.50	410	280	13.00	375	260
5.50	330	235	10.00	265	185	13.00	480	315
6.00	205	140	10.00	340	235			

SUMTALLFER

C/JOANOT MARTORELL 31, 08203 SABADELL

TELF. 937116455

info@sumtallfer.es