

STA^{Srl}

—— Soluzioni Tecnologiche Avanzate



STA 6M3

UNITA' DI MISCELAZIONE E INIEZIONE
grout mixer pump unit

STA 6M3

UNITA' DI MISCELAZIONE E INIEZIONE
grout mixer pump unit



Caratteristiche Tecniche / Technical Features

Prod.maxime / Max hourly mix capacity	5 m ³
Manuel ou automatique / Manual or automatic load and mix system	
Puissance totale / Total electric power	13 KW

Malaxeur / Mixer

Moteur électrique / Electric motor	4 kW - 380 V
Volume utile / Useful capacity	250 lit
Vitesse de rotation / Rotation speed	1500 rpm
Vitesse du fluid / Internal speed flow	600 lit/min

Agitateur / Agitator

Moteur électrique / Electric motor	1,5 kW - 380 V
Volume utile / Useful capacity	500 lit
Vitesse de rotation / Rotation speed	37 rpm
Avec moto-réducteur / With moto reducer	

Centrale hydraulique et injecteur / Powerpack and grouting M4T12

Moteur électrique / Electric motor	7,5 kW - 380 V
HIGH PRESSURE CIRCLE	
Débit maximum d'injection / Maximum grouting flow rate	0 to 60 lit/min
Pression maximum d'injection / Maximum grouting pressure	50 bar
LOW PRESSURE CIRCLE	
Débit maximum d'injection / Maximum grouting flow rate	0 to 120 lit/min
Pression maximum d'injection / Maximum grouting pressure	40 bar
Double gear pump / Double gear pump	

Dimensioni e peso / Overall dimensions and weight

Larghezza / Width:	1.300 mm	Altezza / Height:	1.600 mm
Lunghezza / Length:	1.600 mm	Peso / Weight:	740 Kg