

POWER CUBE

SINGLE AND DUAL FREQUENCY

HPCW



FULL ACCESS
FOR RADIATOR
MAINTENANCE

POWER
OUTLET

CONTROL PANEL
AND POWER
CONTROL
SWITCHBOARD

FULL ACCESS
FOR ENGINE AND
ALTERNATOR
MAINTENANCE

RADIATOR
COMPARTMENT
ISOLATED FROM
THE ENGINE

INTERNAL
SILENCER



HIMOINSA

POWER CUBE

SINGLE AND DUAL FREQUENCY



HPCW

400-230 V_50Hz / 480-277 kW_60Hz | DIESEL



		HPCW-510 D5-6				HPCW-630 D5-6			
		50Hz		60Hz		50Hz		60Hz	
		P.R.P.	STAND-BY	P.R.P.	STAND-BY	P.R.P.	STAND-BY	P.R.P.	STAND-BY
400-230 V_50Hz / 480-277 kW_60Hz DIESEL									
POWER	KVA	510	563	584	644	628	698	697	768
POWER	KW	408	450	468	515	502	558	558	615
RATED SPEED	r.p.m.	1.500		1.800		1.500		1.800	
STANDARD VOLTAGE	V	400/230		480 / 277		400/230		480/277	
AVAILABLE VOLTAGES	V	230T - 230/132 380/220 - 415/240		460/265 - 440/254 - 416 240 - 220/127		380/220 - 415/240		460/265 - 440/254 - 416/240 - 220/127	
RATED AT POWER FACTOR	Cos Phi	0,8				0,8			
ENGINE MODEL		MTU - 10V1600B40S				MTU - 12V1600B40S			
CONSTRUCTIVE VERSION		10FT Container				10FT Container			

HPCW

400-230 V_50Hz | DIESEL

Powered by MTU



GENSET MODEL	TENSION	R.P.M.	KVA		kW		ENGINE MODEL	
			P.R.P.	STAND-BY	P.R.P.	STAND-BY		
HPCW-510 T5	400 V	1.500	510	563	408	450	10V1600G20F	10'
HPCW-660 T5	400 V	1.500	657	713	525	570	12V1600G20F	10'

HPCW

480-277 kW_60Hz | DIESEL

Powered by MTU



GENSET MODEL	TENSION	R.P.M.	KVA		kW		ENGINE MODEL	
			P.R.P.	STAND-BY	P.R.P.	STAND-BY		
HPCW-520 T6	480 V	1.800	587	646	470	517	10V1600G20S	10'
HPCW-620 T6	480 V	1.800	700	772	560	617	12V1600G20S	10'

