



SELF-PROPELLED TURNERS



- Outstanding capacities
- Powerful & robust
- All-terrain manoeuvrability
- High quality of aeration
- Extensive choice of models
- Operator comfort & safety

OVERVIEW



AVAILABLE ACCESSORIES



- Irrigation connections
- Winding/Unwinding device for windrow fleece covers
- Automatic irrigation hose roller
- Spraying device: tank, pump, sprayers
- Wheels or tracks
- Reinforced rotor drum with protection against abrasion

HIGHLIGHTS



EXCELLENT AERATION QUALITY

MENART turners have been specially designed to optimize the aeration and mixing process: large trapezoidal tunnel, powerful rotor drum, no compacting whorl, left-right crossing flow.



OUTSTANDING MACHINE MANOEUVRABILITY

Menart turners can lift up by 50 cm to ensure advancement continuation if there is an obstacle in the windrow. MENART turners are the only ones that can tilt forward or backward for ease and safe movement in slopes. Moreover, the left and the right tracks are independant and can adapt to the ground.



PAD SPACE OPTIMIZED

The SPM turners are equipped with powerful track clearers to improve adherence. Plus, windrows can be bring closer on the site gaining space. On the other hand, MENART turners are big but compact. The turning area is minimized - their 4x4 individual wheel control allows spinning « on itself ».



MAXIMUM DRIVER COMFORT

The cabins are the most modern with all-around visibility and pressurized air conditioning. Joy stick controls are « at hand » for easy use. A fun and intuitive touch screen allows the operator to have all the machine information at a glance. The engine compartments are soundproofed.



OPERATORS SAFETY

MENART turners are easy and safe to maintain thanks to a large and secure platform. The tunnel is equipped with projectiles-protections: rubber curtain and adjustable metallic deflector at the rear.

SIDE-DISCHARGE TURNERS

MENART has developped 2 side-discharge turners: one self-propelled and one tractor-driven. Please, request the specific documentation.



Performances Features

	Units	SPM-36	SPM-47	SPM-55	SPM-63	SPM-73
Engine Power	hp	145	228	275	350	630
Max windrow width	m (ft)	3,6 (11'9")	4,7 (15'5")	5,5 (18')	6,3 (20'8")	7,3 (23'11")
Tunnel height	m (ft)	1,7 (5'6")	1,9 (6'2")	2,1 (6'10")	2,4 (7'10")	2,8 (9'2")
Max windrow height-tunnel raised	m (ft)	2,1 (6'10")	2,4 (7'10")	2,6 (8'2")	2,9 (9'6")	3,3 (10'9")
Indicative capacity	m³/h (yd³/h)	2000 (2600)	3000 (4000)	4000 (5000)	5300 (7000)	7000 (9000)

The compost turner's productivity can vary according to the characteristics of the worked materials. Wide field experience allows MENART turners to provide maximum performance in every circumstance.

References

MENART turners are used in all kind of materials (green waste, household waste, polluted soil, biosolids, sugar cane filter cakes, palm oil EFB, manure, ...



Z.I. Rue Benoît, 31
B-7370 Dour
Tel: +32 (0)65 61 07 60
Fax : +32 (0)65 61 07 49
info@menart.eu
www.menart.eu

Rue Ambroise Croizat
F-59494 Petite Forêt
Tel: +33 (0)3 27 31 03 87
Fax : +33 (0)3 27 31 11 36
info@menart.eu
www.menart.eu



Please request documentation on our other products: shredders, turners, mobile and stationary screens, etc.