

GF11 Fiberglass rod Ø 11 mm

for pipe diameter 60 - 250 mm, incl. double run-out-system

Item. no. **10092** | **10093** | **10094** | **10095** | **10096** | **10097**

VIDEO

GF11

[Click here Video](#)

KG 580
Ø 11 mm

[Click here Product-information](#)

Rod tip: Shackle, stainless steel, RTG Ø 12 mm thread, screwed to strang

Rod end: Ending joint, stainless steel, RTG Ø 12 mm thread

Double run-out-system
(Quick run and automatic run-out brake)

Quick run with mounted rollers

Automatic run-out brake rollers

Meter counter with hardened thumb wheel

Additional option: Adaptable leading heads

6-digit roller counter with meter and 10 cm steps

13-parts flexible leading head-set

Rod	Rec. pipe diameter	Bending radius w. e. joint	Bending radius rod	Breaking load	Total breaking load
Ø					
11 mm	60 - 250 mm	770 mm	210 mm	6200 kg	580 kg

DATA						
Recommended trade price in EURO / excluding VAT						
ITEM. NO.	10092	10093	10094	10095	10096	10097
PRICE €	758,00	831,00	936,00	1118,00	1306,00	1410,00
LENGTH	100 m	120 m	150 m	200 m	250 m	300 m
WEIGHT KG	37,00 kg	40,00 kg	45,21 kg	53,07 kg	58,00 kg	67,69 kg
MATERIAL ROD	Fiberglass core with PP sheath					
BENDING RADIUS	770 mm					
PIPE Ø	optimal from 60 - 250 mm					
DIMENSION	L 1140 mm W 550 mm H 1200 mm					
TOTAL BREAKING LOAD	580 kg					

DESCRIPTION

GF11 Glass fibre rod Ø 11 mm – cable pulling tool with robust, mobile steel reel (KTL-coated/powder-coated) Ø 1000 mm, integrated metre counter and RUNPOTEC threaded RTG Ø 12 mm. The integrated metre counter, featuring a mechanical counter mechanism, a hardened knurled wheel and a 6-digit roller counter, enables precise length measurement with metre and 10-cm displays. The new dual-feed system, with an automatic feed brake and quick-release feed, allows for controlled and efficient operation. The additional locking brake secures the reel and prevents accidental rotation. The shackle features an adapter thread to RTG Ø 6 mm, allowing various accessories such as RUNPOSTICKS, guide probes, cable pulling socks and the RC2 or RC3 inspection cameras to be easily attached. The fiberglass rod has a breaking load of up to 6200 kg. The total breaking load, including the end sleeve, is 580 kg. The bending radius is 210 mm on the rod and 770 mm with the sleeve.

Ideal application: for pipe diameters from 80 mm to 250 mm.

Scope of supply: 1 x GF11 Fiberglass rod Ø 11 mm, stainless steel ending joint (start/end) 1 x steel reel Ø 1000 mm mobile incl. double run-out-system, 1 x meter counter, 1 x shackle

ADVANTAGES

- Incl. steel reel and meter counter
- Double run-out system (automatic run-out brake and fast run-out)
- Additional parking brake
- Fiberglass rod breaking load 6200 kg
- Total breaking load 580 kg
- Bending radius only rod 210 mm
- Bending radius with ending joint 770 mm

INFORMATION

Compatible with:

RC2 Inspection camera
50 m - Item no.: 10141



RC3 Inspection camera (digital)
15 m - Item no. 10214

