

Line
guimadira
Proven solution



PRESS BRAKES
Double your profits, cut your costs!

by **adira**


Press Brakes



Accurate | Competitive | Cost effective | Productivity | Sustentable

Synchronized PM 13530 HEXA C®

Press Brakes PM		PM 13530	PM 13540	PM 16030	PM 16040	PM 22040
Bending Capacity	kN	1350	1350	1600	1600	2200
Working length	mm	3050	4050	3050	4050	4050
Distance between housings	mm	2550	3150	2550	3150	3150
Max. stroke	mm	250	250	250	250	250
Max open height w/ tools	mm	500	500	500	500	500
Throat depth	mm	400	400	400	400	400
Motor power	kW	7,5	7,5	9	9	15
Approach speed	mm/s	120	120	120	120	100
Working speed (max.)	mm/s	7	7	7	7	8
Return speed	mm/s	70	70	70	70	85
X axis stroke	mm	625	625	625	625	625
X axis speed	mm/s	350	350	350	350	350
R axis stroke	mm	150	150	150	150	150
R axis speed	mm/s	40	40	40	40	40
Z1-Z2 axis stroke	mm	90 to 2150	90 to 2750	90 to 2150	90 to 2750	90 to 2750
Z1-Z2 axis speed	mm/s	600	600	600	600	600



ADIRA

Rua António Bessa Leite, 976/1106
4150-072 Porto > PORTUGAL
Telf. + 351 22 619 27 00
Fax. + 351 22 619 27 01
E-mail: guimadira@adira.pt



DC/MAP-C-157-I-12/10