



PERFORADORA AUTOMÁTICA

NAV - PERF 600



Code	Pitch	Dia me ter	Holes	Hole distance	Die Pattern Style
A	3:1	4 × 4mm (0.156 × 0.156)	72	8.47	
B	4:1	φ 4.2mm (0.165)	96	6.35	
C	4:1	5.5 × 4.0mm (0.217 × 0.156)	96	6.35	
D	2:1	6.35 × 6.35mm (0.250 × 0.250)	48	12.7	
E	14:25mm	8 × 3mm (0.312 × 0.125)	43	14.25	
F	4:1	4.5 × 3.6mm (0.177 × 0.142)	96	6.35	
G	5:1	φ 3.2mm (0.126)	119	5	
H	3:1	φ 4mm (0.156)	72	8.47	
I	3:1	φ 4.2mm (0.165)	70	8.47	
J	3:1	φ 4.2mm (0.165)	72	8.47	
K	3:1	4 × 4mm (0.156 × 0.156)	70	8.47	
L	3:1	φ 5mm (0.197 × 0.197)	72	8.47	
M	25mm		24	25	
N	45mm		14	45	
O	4:1	φ 4 × 3mm (0.156 × 0.125)	96	6.35	
P	5:1	φ 4 × 3mm (0.156 × 0.125)	119	5.08	
Q	2:1	5.5 × 5.5mm (0.217 × 0.217)	48	12.7	
R	2:1	φ 5mm (0.197 × 0.197)	48	12.7	
S	6	φ 4.2mm	102	6	
T	2:1	3.5 × 5.5mm	48	12.7	
U	2:1	φ 6.4mm	48	12.7	
V	2:1	6 × 6mm	48	12.7	
W	3:1	φ 4.5mm	72	8.47	
X	3:1	φ 4.5mm	70	8.47	

Máquina para trabajo intensivo (24H).